

MATERIAL SAFETY DATA SHEET

This Material Safety Data Sheet complies with the Canadian Controlled Products Act
NOTE: THE FOLLOWING INFORMATION PROVIDED IS FOR THE PRODUCT CONCENTRATE ONLY, NOT FOR USE-DILUTIONS

SECTION 1 – PRODUCT IDENTIFICATION								
		SECTION I	- PRODUCT IDE	VIIFICATION				
PRODUCT IDENTIFIER: PI	REP-RITE							
PRODUCT USE: He	avy Duty Me	etal Surface P	reparation Cleaner					
Ur Sເ Er	elocity Chem hit #1, 9515- hrey, B.C. Vonergency Te csimile: (604	190 th St., 4N-3S1 lephone: (604	In case of transporation emergency or product spill, contact: In Canada- CANUTEC @ 613-996-6666 (24 hrs.)					
SECTION 2 – HAZARDOUS INGREDIENTS								
HAZARDOUS INGREDIENTS	% (W/W)	CAS NUMBER	LD50	LC50	EXPOSURE LIMITS			
Potssium Hydroxide	10-30	1310-58-3	365 mg/kg (oral, rat)	Not available	OSHA(PEL) & ACGIH (TLV)= 2mg/m3(ceiling)			
Tetrapotassium Pyrophosphate	5-10	7320-34-5	>1000 mg/kg (oral,rat) > 4640 mg/kg (skin,rabbit)	Not available	Not established			
Ethylene Glycol Monobutyl Ether	1-5	111-76-2	470mg/kg (oral,rat) 220mg/kg (skin,rabbit)	450ppm (inhal.,4hrs, rat)	OSHA(PEL)= 50ppm,skin ACGIH(TWA)= 20ppm,skin IDHL= 700ppm			
acid, tetrasodium salt (oral,ra > 5g/k		3030 mg/kg (oral,rat) > 5g/kg (skin, rabbit)	Not available	Not established				
SECTION 3 – PHYSICAL DATA								

Physical state: liquid Solubility: soluble

Odour and Appearance: clear, mild odor

pH (100%) @ 20°C: 13.0-14.0 Specific Gravity @ 20°C: 1.27

Odour Threshold (ppm): not established

Vapour Density: not determined
Vapour Pressure: not determined
Evaporation Rate: not determined
Boiling Point (°C): not determined
Freezing Point (°C): not determined

Coefficient of water/oil distribution: Greater than

1

PREP-RITE

SECTION 4 - FIRE AND EXPLOSION DATA

Flammability: No, product is non-flammable.

If yes, under what condition: Not applicable.

Means of Extinction: Dry chemical, alcohol foam, CO₂, water spray. The product is not flammable. Use extinguishing media suitable for surrounding fires.

Special Fire Fighting Procedures: Wear NIOSH/OSHA approved, self contained breathing apparatus for fire fighting situations. Use water spray to cool all nearby fire exposed surfaces.

Explosion Data-

Sensitivity to impact: None

Sensitivity to static discharge: None

Flash Point (°C) and method: not applicable

Upper Flammable limit (% volume): not applicable
Lower Flammable limit (% volume): not applicable

Autoignition temperature (°C): not applicable

Usual Fire Hazards: Prolonged contact with sensitive metals like aluminum may form flammable hygrogen gas.

Hazardous combustion products: may liberate carbon/nitrogen/phosphorous oxides, and other toxic organic vapours.

SECTION 5 – REACTIVITY DATA

Chemical Stability: yes, stable under normal storage conditions

If no, under what conditions:

Incompatibility with other substances: yes

If so, under what conditions: strong acids and oxidizers, and reacts with sensitive metals such as zinc or aluminum to form flammable hydrogen gas.

Reactivity, and under what conditions: none known

Hazardous Decomposition Products: may liberate carbon/nitrogen/phophorous oxides upon thermal decomposition.

SECTION 6 – TOXICOLOGICAL PROPERTIES

Primary route of entry: skin and eye contact, skin absorption, inhalation

Effects of Acute Exposure to Product: Product exposure can cause severe irritation or burns to skin and eyes. Inhaling mist or vapors can cause immediate irritation, burns or discomfort to respiratory system, headaches, nausea, etc. Also, may be harmful if absorbed through skin.

Effects of Chronic Exposure to Product: Prolonged exposure may cause skin dermatitis and respiratory disorder. May also cause blood, kidney and liver disorders through repeated exposure of Ethylene glycol Monobutyl ether (based on animal test data).

Exposure Limits: see Section 2 under Hazardous Ingredients

Irritancy of Product: corrosive to skin, eyes and

respiratory system.

Sensitization: none known

Reproductive Toxicity: none known

Mutagenicity: none known

Carcinogenicity: glycol ether monobutyl ether is classified as Group 3 (Unclassifiable as to carcinogenicity in humans) under IARC and A3 (confirmed animal carcinogen with unknown revelence to humans) under ACGIH.

Teratogenicity: none known

Synergistic Products: none known

PREP-RITE

SECTION 7 - PREVENTATIVE MEASURES

Respiratory Protection: Use a NIOSH/OSHA approved for alkaline mist/dust and organic vapor respirator if mists or vapors are present.

Gloves: butyl or natural rubber, nitrile, neoprene

Eye Protection: splash proof chemical goggles or face

shield.

Footwear: rubber shoes

Clothing: long sleeve coveralls

Other: rubber apron

Engineering Controls: General ventilation for normal operating conditions or local exhaust for confined areas.

Leak and Spill Procedures: Wear protective equipment. Contain spill. Prevent runoff to drains or sewers. Recover material by vacuum or pump into a suitable waste container. Reuse material if possible, or otherwise neutralize with acid before disposal. Dispose in accordance with local regulations.

Waste Disposal: Dispose of in accordance with local environmental regulations.

Handling Procedures and Equipment: Use good hygiene practices. Avoid contact with eyes, skin and clothing. Avoid inhaling mists/vapors. Safety shower and eye wash station should be available in the immediate work area.

Storage Requirements: Store in a cool, dry place away from incompatibles. Do not mix with any other chemicals. Keep container closed when not in use. Keep from freezing and temperatures below 30°C.

Special Shipping Information:

WHMIS Classification: D2B, E

TDG Classification: Corrosive Liquid, N.O.S. (Potassium Hydroxide Mixture), Class 8, UN 1760, P.G. III

SECTION 8 - FIRST AID MEASURES

Inhalation: Remove victim to fresh air, apply artificial respiration if necessary. Seek medical help.

Ingestion: Give large amounts of water if conscious. Do not induce vomiting. Get medical help immediately.

Skin Contact: Wash thoroughly with water for 15 minutes. If irritation persist, seek medical attention. Eye Contact:

Flush immediately with water for 15-20 minutes. Seek medical help.

SECTION 9 - OTHER INFORMATION								
REVISIONS:	December 14, 2007	SUPERCEDES:	November 21, 2006					
PREPARED BY:	Technical Department (Customer Service phone number: 604-881-4700)							
DISCLAIMER:	The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. Velocity Chemicals Ltd. expressly disclaims all expressed or implied warranties and assumes no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.							